

## PVC COATED LIQUIDTIGHT CONNECTORS - STRAIGHT

### Description:


Calbond PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is sized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings are provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

### Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 4", the length of the sleeve extension(s) shall be at least 2"
- Available in straight, 45 degree or 90 degree body configurations

### Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



Straight						
Item Number	Trade Size	A	B	C	Weight Per 100 (lbs)	
PV0300LT38	3/8"	1.24	1.88	0.56	20	
PV0500LT50	1/2"	1.46	2.06	0.56	20	
PV0700LT75	3/4"	1.74	2.38	0.56	30	
PV1000LT100	1"	1.96	3.06	0.75	40	
PV1200LT125	1-1/4"	2.36	3.75	0.81	80	
PV1500LT150	1-1/2"	2.80	4.19	0.81	90	
PV2000LT200	2"	3.33	5.06	0.88	170	
PV2500LT250	2-1/2"	3.83	6.13	1.00	300	
PV3000LT300	3"	4.58	6.25	1.00	420	
PV4000LT400	4"	5.58	6.50	1.13	620	