

Building connections that last™



# Anvil®

## Pipe Fittings & Steel Nipples



# BUILDING CONNECTIONS THAT LAST



For over 160 years, Anvil has worked diligently to build a strong, vibrant tradition of making connections — pipe to pipe and people to people.

We pride ourselves in providing the finest quality pipe products and services with integrity and dedication to superior customer service at all levels.



We provide expertise and product solutions for a wide range of applications, from plumbing, mechanical, HVAC, industrial and fire protection to mining, oil and gas. Our comprehensive line of products includes: grooved pipe couplings, grooved and plain-end fittings, valves, cast and malleable iron fittings, forged steel fittings, steel pipe nipples and couplings, pipe hangers and supports, channel and strut fittings, mining and oil field fittings, along with much more.

As an additional benefit to our customers, Anvil offers a complete and comprehensive Design Services Analysis for mechanical equipment rooms, to help you determine the most effective and cost-efficient piping solutions.



Anvil is a proud member of the United States Green Building Council (USGBC). Go to the Anvil website to obtain manufacturer recycled certificates and other Green information.

At Anvil, we believe that responsive and accessible customer support is what makes the difference between simply delivering products — and delivering solutions.



# Pipe Fittings

## History

For over 160 years, Anvil has been a trusted name in piping solutions by consistently providing quality products, service, and support to the PVF industry. Our ability to provide cost-efficient piping packages that are tailored to individual markets is unmatched in the industry. From plumbing, mechanical, and fire protection, to mining, oil and gas, our innovative responses are designed to meet your specific demands.

## Products

Our manufacturing facilities produce an unrivaled package of piping products, while setting a world-wide industry standard for quality and dependability. Our ISO certified facilities use recycled materials in the manufacturing of our product as well as being a proud member of the USGBC.

## Distribution Channel

The wholesaler has always been the key to Anvil's business. Our dedication to the wholesale trade is the driving force for our services and these relationships remain a primary focus of Anvil's innovation. Our value-added services including a proprietary suite of inventory management tools signifies a strong commitment to our customers needs.

## Customer Service

Having major distribution centers located throughout North America, you can count on getting the product you need - when you need it. Customer satisfaction has always been Anvil's #1 objective. Our experienced Sales and Customer Service Teams are knowledgeable and eager to serve our customers, validating our company's motto "Building Connections that Last."

## Pipe Fitting Product Line

- Malleable Iron Pipe Fittings  
Threaded Fittings  
Class 150 (Standard)  
Class 300 (XS/XH)
- Cast Iron Pipe Fittings  
Threaded Fittings  
Class 125 (Standard)  
Class 250 (Extra Heavy)  
Flanged Fittings  
Class 125 (Standard)  
Drainage Fittings
- Small Steel Fittings  
Merchant Steel
- Pipe Nipples  
Seamless and Welded
- Pipe Couplings
- Forged Steel Pipe Fittings  
Threaded Fittings  
Class 2000  
Class 3000  
Class 6000  
Socket Weld Fittings  
Class 3000  
Class 6000
- Anvilets
- Catawissa Products
- J.B. Smith Products

# TABLE OF CONTENTS

## Malleable Iron – Pipe Nipples & Pipe Couplings

### Malleable Iron

Technical Data .....	16
<b>CLASS 150 (STANDARD)</b>	
Fig. 1101 90° Elbow .....	17
Fig. 1101R Reducing Elbow .....	17
Fig. 1102 45° Elbow .....	18
Fig. 1103 (Straight) & Fig. 1103R (Reducing) 90° Street Elbow .....	18
Fig. 1104 45° Street Elbow .....	19
Fig. 1105 Straight Tee .....	19
Fig. 1105R Reducing Tee .....	20 - 22
Fig. 1106 (Straight) & Fig. 1106R (Reducing) Street or Service Tee .....	23
Fig. 1107 Cross .....	23
Fig. 1108 45° Y-Branch or Lateral .....	23
Fig. 1119 Return Bend Open Pattern, R.H. ....	24
Fig. 1121 Coupling .....	24
Fig. 1124 Cap .....	24
Fig. 1125 Reducer .....	25
Fig. 1134 Hex Locknut .....	26
Fig. 1190 Floor Flange (Ductile Iron) .....	26
Fig. 1133 Waste Nut .....	26
Fig. 1138 Extension Piece .....	26
<b>CLASS 300 (XS/XH)</b>	
Fig. 1161 90° Elbow Straight .....	27
Fig. 1161R 90° Reducing Elbow .....	27
Fig. 1160 45° Street Elbow .....	27
Fig. 1162 45° Elbow .....	28
Fig. 1170 90° Street Elbow .....	28
Fig. 1164 Straight Tee .....	28
Fig. 1164R Reducing Tee .....	29
Fig. 1165 Cross .....	29
Fig. 1166 Coupling .....	30
Fig. 1167 Reducer .....	30
Fig. 1163 Cap .....	31
Fig. 390 Square Countersunk Plug .....	31
<b>ALL IRON UNIONS</b>	
Fig. J-3300 All Iron Union Class 300 .....	31
<b>MALLEABLE IRON UNIONS – CLASS 150; 250; 300</b>	
Fig. 463 Class 150 Union .....	32
Fig. 554 Class 250 Union .....	32
Fig. 459 Class 300 Union .....	32
Fig. 551 Class 300 Union male & female .....	32
Fig. 552 Class 300 90° Female Union .....	33
Fig. 832 Dart Union Bronze Seat to Bronze Seat Union .....	33
<b>MALLEABLE HEX AND FACE BUSHING</b>	
Fig. 383 Hex Bushing .....	34
Fig. 385 Face Bushing .....	34

### Cast Iron

Technical Data .....	35
<b>THREADED FITTINGS – CLASS 125 (STANDARD)</b>	
Fig. 351 90° Elbow .....	36
Fig. 371 90° Elbow, Flange & Screw .....	36
Fig. 356 (Straight) & Fig. 356R (Reducing) 45° Elbow .....	37
Fig. 356A 22½° Elbow .....	37
Fig. 352 90° Elbow, Reducing .....	38
Fig. 358 Tee .....	39
Fig. 359 Tee, Reducing .....	39 - 43
Fig. 360 Cross .....	44
Fig. 361 Cross, Reducing .....	44
Fig. 366 Screwed Hex Coupling .....	45
Fig. 487 Flanged Union Gasket Type .....	45
Fig. 367 Concentric Reducer .....	46
Fig. 368 Eccentric Reducer .....	47
Fig. 383 Hex Bushing .....	48 - 49
Fig. 385 Face Bushing .....	49
Fig. 387 Square Head Plug, Cored .....	50
Fig. 388 Square Head Plug, Solid .....	50
Fig. 389 Bar Plug, Cored .....	50
Fig. 380 Bar Plug, Solid .....	50
Fig. 390 Countersunk Plug .....	50
Fig. 381 Cap .....	50
Fig. 370 Locknut .....	51
<b>THREADED FITTINGS – CLASS 250 (EXTRA HEAVY)</b>	
Fig. 421 90° Elbow .....	51
Fig. 424 45° Elbow .....	51
Fig. 425 Tee .....	52
Fig. 426 Reducing Tee .....	52
<b>DRAINAGE FITTINGS</b>	
Technical Data .....	53, 56
Fig. 701 90° Short Turn Elbow .....	54
Fig. 701R 90° Reducing Short Turn Elbow .....	54
Fig. 702 90° Long Turn Elbow .....	54
Fig. 702A 90° Extra Long Turn Elbow .....	54
Fig. 703 60° Short Turn Elbow .....	54
Fig. 705 45° Short Turn Elbow .....	55
Fig. 706 45° Long Turn Elbow .....	55
Fig. 707 22½° Elbow .....	55
Fig. 708 11¼° Elbow .....	55
Fig. 718 90° Street Elbow .....	57
Fig. 719 45° Street Elbow .....	57
Fig. 722 Tee .....	57
Fig. 723 Reducing Tee .....	57
Fig. 726 90° Short Turn Y-Branch Tee Pattern .....	58
Fig. 727 90° Reducing Short Turn Y-Branch Tee Pattern .....	58
Fig. 729 Reducing Double Short Turn Tee .....	58
Fig. 730 90° Long Turn Y-Branch Tee Pattern .....	58
Fig. 731 90° Reducing Long Turn Y-Branch Tee Pattern .....	59

### Cast Iron (continued)

Fig. 734 45° Y-Branch .....	59
Fig. 735 45° Reducing Y-Branch .....	59
Fig. 736 45° Double Y-Branch .....	59
Fig. 753 Coupling .....	60
Fig. 744 Tucker Connection .....	60
Fig. 752 P-Trap .....	60
Fig. 754 Bath P-Trap .....	60
<b>FLANGED FITTINGS – CLASS 125 (STANDARD)</b>	
Technical Data .....	61, 74
Fig. 801 90° Flanged Elbow .....	62
Fig. 802 45° Flanged Elbow .....	62
Fig. 803 90° Reducing Flanged Elbow .....	63
Fig. 804 90° Long Radius Flanged Elbow .....	63
Fig. 805 90° Flanged Base Elbow .....	64
Fig. 811 Flanged Tee .....	64
Fig. 812 Flanged Reducing Tee .....	65
Fig. 821 Flanged Cross .....	66
Fig. 823 Flanged Lateral .....	66
Fig. 825 Flanged Concentric Reducer .....	67
Fig. 826 Flanged Eccentric Reducer .....	67
<b>IRON FLANGES – CLASS 125 (STANDARD)</b>	
Fig. 1011 Companion Flange .....	68
Fig. 1018 Blind Flange .....	68
Fig. 1016 Reducing Flange .....	69
<b>IRON FLANGES – CLASS 250 (EXTRA HEAVY)</b>	
Fig. 1025 Companion Flange .....	70
Fig. 1030 Reducing Flange .....	70
Fig. 1021 Blind Flange .....	70
<b>THREADED FITTING - SAFETY VALVE DISCHARGE ELBOW</b>	
Fig. 1538 Screwed Cast Iron .....	71
<b>Small Steel Fittings</b>	
<b>MERCHANT STEEL</b>	
Hex Bushings .....	73
Countersunk Plugs (Square and Hex Socket) .....	73
Flush Bushings .....	74
Caps .....	74
Solid Square Head Plugs .....	74
<b>Pipe Nipples and Pipe Couplings</b>	
Technical Data .....	75
Seamless Pipe Nipples .....	76
Welded Pipe Nipples .....	77 - 79
Special Design Pipe Nipples .....	80 - 81
Fig. 336 Standard, Full & Half Couplings .....	82
Fig. 337 Extra Strong (XS), Full & Half Couplings .....	83
Fig. 346 Standard, Right & Left Couplings .....	84
Fig. 347 Extra Strong (XS), Right & Left Couplings .....	84
Fig. 348 API Line Pipe Coupling .....	85

## Pipe Nipples & Pipe Couplings – Technical Data

### Pipe Nipples and Pipe Couplings (continued)

Fig. 349 Water Well Reamed & Drifted Coupling.....	86
Fig. 350 #9 Drive Coupling.....	86
Fig. 379 Shallow Well Coupling.....	86

### Forged Steel

Technical Data.....	87
---------------------	----

#### THREADED – CLASS 2000

Fig. 2101 90° Elbow.....	88
Fig. 2102 45° Elbow.....	88
Fig. 2103 Tee.....	89
Fig. 2104 Cross.....	89

#### THREADED – CLASS 3000

Fig. 2111 90° Elbow.....	90
Fig. 2112 45° Elbow.....	90
Fig. 2114 Tee.....	90
Fig. 2115 Cross.....	91
Fig. 2113 90° Street Elbow.....	91
Fig. 2116 Lateral.....	91
Fig. 2117 Coupling.....	92
Fig. 2119 Half Coupling.....	92
Fig. 2118 Reducing Coupling.....	93
Fig. 2120 Pipe Cap.....	93

#### THREADED – CLASS 6000

Fig. 2131 90° Elbow.....	94
Fig. 2132 45° Elbow.....	94
Fig. 2134 Tee.....	94
Fig. 2135 Cross.....	95
Fig. 2133 90° Street Elbow.....	95
Fig. 2136 Lateral.....	95
Fig. 2137 Coupling.....	96
Fig. 2141 Half Coupling.....	96
Fig. 2138 Reducing Coupling.....	97
Fig. 2143 Pipe Cap.....	97

#### SOCKET WELD – CLASS 3000

Fig. 2150 90° Elbow.....	98
Fig. 2151 45° Elbow.....	98
Fig. 2152 Tee.....	99
Fig. 2153 Cross.....	99
Fig. 2158 Lateral.....	100
Fig. 2154 Coupling.....	100
Fig. 2155 Half Coupling.....	101
Fig. 2156 Reducing Coupling.....	101
Fig. 2157 Pipe Cap.....	102

#### SOCKET WELD – CLASS 6000

Fig. 2170 90° Elbow.....	103
Fig. 2171 45° Elbow.....	103
Fig. 2172 Tee.....	104
Fig. 2173 Cross.....	104
Fig. 2178 Lateral.....	104
Fig. 2174 Coupling.....	105
Fig. 2175 Half Coupling.....	105
Fig. 2176 Reducing Coupling.....	106

### Forged Steel (continued)

Fig. 2177 Pipe Cap.....	106
-------------------------	-----

#### HIGH PRESSURE PLUGS & BUSHINGS

Fig. 2122 Square Head Plug.....	107
Fig. 2142 Hex Head Plug.....	107
Fig. 2121 Round Head Plug.....	107
Fig. 2139 Hex Head Bushing.....	108
Fig. 2140 Flush Bushing.....	108

#### SOCKET-WELD REDUCER INSERTS

Class 3000.....	109
Class 6000.....	110

#### FORGED STEEL UNIONS

Fig. 2125 Class 3000 Threaded Union.....	111
Fig. 2126 Class 3000 Socket-Weld Union.....	111
Fig. 2127 Class 6000 Threaded Union.....	112
Fig. 2128 Class 6000 Socket-Weld Union.....	112

#### Anvilets

Technical Data.....	113, 118
Universal Forged Steel Buttweld Anvilets..	114 - 115
Universal Forged Steel Threaded Anvilets....	116
Universal Forged Steel Socket-Weld Anvilets..	117
Universal Elbowlet.....	119
Lateral Anvilet.....	120
Flat Anvilet.....	121

#### Catawissa

Technical Data.....	122
Fig. 100 Hammer Union.....	123
Fig. 200 Hammer Union.....	124
Fig. 206 Hammer Union.....	125
Fig. 211 Insulating Union.....	126
Fig. 300 Flat-Face Union.....	127
Fig. 301 Steam Service Union.....	128
Fig. 400 Hammer Union.....	128
Fig. 602 Hammer Union.....	129
Fig. 602 Hammer Union (Buttweld Ends).....	129
Fig. 607 Well Service Union.....	130
Fig. 1502 Hammer Union.....	131
Catawissa Quick Reference Chart.....	132

#### J.B. Smith Products

Technical Data.....	134 - 135, 142
Concentric Swage Nipples.....	136 - 137
Eccentric Swage Nipple.....	138
Stainless & Alloy Steel Swage Nipple.....	139
Carbon Steel Bull Plug.....	140
Solid Refinery Plug.....	140
Adapter Nipples.....	141

#### J.B.S. Oil Country

Large End Upset Reduced to Regular Swage Nipple.....	143
Large End Non-Upset Reduced to Upset Swage Nipple.....	143
Swage Nipple Oil Country Tubing & Casing non EUE ends.....	144

### J.B.S. Oil Country (continued)

Tubing Bull Plug.....	145
Casing Bull Plug.....	145
API Bull Plug Female.....	145
Bell Nipple.....	146
Tubing Nipple (Standard Weight).....	146
Tubing Nipple (Extra Heavy Weight).....	146
Oil Country Casing Nipple.....	147
API Casing Coupling (Short Thread).....	148
API Casing Coupling (Long Thread).....	148
Combination Coupling J-55.....	148
Sub Tubing Couplings J-55.....	149
API Tubing Coupling.....	149
Special Clearance Tubing Coupling.....	149
Chambers/Pressure Vessels.....	150

#### Oil Country Fittings

Pumping Tee.....	151
Coated Products.....	152

#### Technical Data

General Assembly of Threaded Fittings.....	153
Conditions and Terms of Sale.....	154
Engineering Information.....	155
Figure Number Index.....	156

Anvil reserves the right to make specification changes without notice. While every effort has been made to assure the accuracy of information contained in this catalog at the time of publication, we cannot accept responsibility for inaccuracies resulting from undetected errors or omissions.

# PICTORIAL TABLE OF CONTENTS

## Malleable Iron

### MALLEABLE IRON FITTINGS – CLASS 150 (STANDARD)

 <p><b>Fig. 1101</b> 90° Elbow Size Range: 1/8" thru 6" Page 17</p>	 <p><b>Fig. 1101R</b> 90° Reducing Elbow Size Range: 1/4" x 1/8" thru 4" x 3" Page 17</p>	 <p><b>Fig. 1102</b> 45° Elbow Size Range: 1/8" thru 6" Page 18</p>	 <p><b>Fig. 1103 &amp; 1103R</b> 90° Street Elbow (Straight &amp; Reducing) Size Range: 1/8" thru 4" (Straight) 1/2" x 3/8" thru 2" x 1 1/2" (Reducing) Page 18</p>	 <p><b>Fig. 1104</b> 45° Street Elbow Size Range: 1/8" thru 2" Page 19</p>	 <p><b>Fig. 1105</b> Straight Tee Size Range: 1/8" thru 6" Page 19</p>
 <p><b>Fig. 1105R</b> Reducing Tee Size Range: 1/8" x 1/8" x 1/4" thru 4" x 4" x 3" Page 20 - 22</p>	 <p><b>Fig. 1106 &amp; 1106R</b> Street or Service Tee (Straight &amp; Reducing) Size Range: 1/4" thru 2" (Straight) 1 1/4" x 1" x 1 1/4" (Reducing) Page 23</p>	 <p><b>Fig. 1107</b> Cross Size Range: 1/8" thru 4" Page 23</p>	 <p><b>Fig. 1108</b> 45° Y-Branch or Lateral Size Range: 3/8" thru 4" Page 23</p>	 <p><b>Fig. 1119</b> Return Bend - Open Pattern, R.H. Size Range: 1/2" thru 2" Page 24</p>	 <p><b>Fig. 1121</b> Coupling Size Range: 1/8" thru 4" Page 24</p>
 <p><b>Fig. 1124</b> Cap Size Range: 1/2" thru 6" Page 24</p>	 <p><b>Fig. 1125</b> Reducer Size Range: 1/4" x 1/8" thru 6" x 4" Page 25</p>	 <p><b>Fig. 1134</b> Hex Locknut Size Range: 1/4" thru 2" Page 26</p>	 <p><b>Fig. 1190</b> Floor Flange (Ductile Iron) Size Range: 1/4" thru 2" Page 26</p>	 <p><b>Fig. 1133</b> Waste Nut Size Range: 1/2" &amp; 3/4" Page 26</p>	 <p><b>Fig. 1138</b> Extension Piece Size Range: 1/2" thru 1" Page 26</p>

### MALLEABLE IRON FITTINGS – CLASS 300 (XS/XH)

 <p><b>Fig. 1161</b> 90° Elbow Size Range: 1/4" thru 4" Page 27</p>	 <p><b>Fig. 1161R</b> 90° Reducing Elbow Size Range: 3/8" x 1/4" thru 2" x 1 1/2" Page 27</p>	 <p><b>Fig. 1160</b> 45° Street Elbow Size Range: 1/2" thru 2" Page 27</p>	 <p><b>Fig. 1162</b> 45° Elbow Size Range: 1/4" thru 4" Page 28</p>	 <p><b>Fig. 1170</b> 90° Street Elbow Size Range: 1/4" thru 3" Page 28</p>	 <p><b>Fig. 1164</b> Straight Tee Size Range: 1/4" thru 4" Page 28</p>
 <p><b>Fig. 1164R</b> Reducing Tee Size Range: 3/8" x 3/8" x 1/4" thru 3" x 3" x 2" Page 29</p>	 <p><b>Fig. 1165</b> Cross Size Range: 1/4" thru 2" Page 29</p>	 <p><b>Fig. 1166</b> Coupling Size Range: 1/4" thru 3" Page 30</p>	 <p><b>Fig. 1167</b> Reducer Size Range: 3/8" x 1/4" thru 4" x 3" Page 30</p>	 <p><b>Fig. 1163</b> Cap Size Range: 1/4" thru 3" Page 31</p>	 <p><b>Fig. 390</b> Square Countersunk Plugs Size Range: 1/2" &amp; 3/4" Page 31</p>

## Malleable Iron (Continued) – Cast Iron

### MALLEABLE IRON UNIONS (CLASS 150, 250, 300)

 <p><b>Fig. 463</b> Class 150 Union Size Range: 1/8" thru 3" Page 32</p>	 <p><b>Fig. 554</b> Class 250 Union Size Range: 1/8" thru 4" Page 32</p>	 <p><b>Fig. 459</b> Class 300 Union Size Range: 1/8" thru 4" Page 32</p>
 <p><b>Fig. 551</b> Class 300 Union Male &amp; Female Size Range: 1/2" thru 2" Page 32</p>	 <p><b>Fig. 552</b> Class 300 90° Elbow Female Union Size Range: 3/8" thru 1" Page 33</p>	 <p><b>Fig. 832</b> Dart Union Bronze to Bronze Seat Union Size Range: 3/8" thru 2" Page 33</p>

### ALL IRON UNION

 <p><b>Fig. J-3300</b> All Iron Union Class 300 Size Range: 1/4" thru 3" Page 31</p>
--

### MALLEABLE HEX AND FACE BUSHING

 <p><b>Fig. 383</b> Hex Bushing Size Range: 3/4" x 1/8" thru 2 1/2" x 2" Page 34</p>	 <p><b>Fig. 385</b> Face Bushing Size Range: 3/4" x 3/8" thru 3" x 2 1/2" Page 34</p>
--	--

### CAST IRON THREADED FITTINGS – CLASS 125 (STANDARD)

 <p><b>Fig. 351</b> 90° Elbow Size Range: 1/4" thru 8" Page 36</p>	 <p><b>Fig. 371</b> 90° Elbow - Flange &amp; Screw Size Range: 2 1/2" thru 6" Page 36</p>	 <p><b>Fig. 356</b> 45° Elbow Size Range: 1/4" thru 8" Page 37</p>	 <p><b>Fig. 356R</b> 45° Reducing Elbow Size Range: 1" x 1/2" Page 37</p>	 <p><b>Fig. 356A</b> 22 1/2° Elbow Size Range: 3/4" thru 2 1/2" Page 37</p>	 <p><b>Fig. 352</b> 90° Reducing Elbow Size Range: 1/2" x 1/4" thru 6" x 5" Page 38</p>
 <p><b>Fig. 358</b> Tee Size Range: 1/4" thru 8" Page 39</p>	 <p><b>Fig. 359</b> Reducing Tee Size Range: 1/2" x 1/2" x 1/4" thru 6" x 6" x 5" Page 39 - 43</p>	 <p><b>Fig. 360</b> Cross Size Range: 1/2" thru 6" Page 44</p>	 <p><b>Fig. 361</b> Cross Reducing Size Range: 1" x 1" x 3/4" x 3/4" thru 4" x 4" x 2" x 2" Page 44</p>	 <p><b>Fig. 366</b> Screwed Hex Coupling Size: 1" Page 45</p>	 <p><b>Fig. 487</b> Flanged Union Gasket Type Size Range: 1/2" thru 8" Page 45</p>
 <p><b>Fig. 367</b> Concentric Reducer Size Range: 3/4" x 1/2" thru 8" x 6" Page 46</p>	 <p><b>Fig. 368</b> Eccentric Reducer Size Range: 3/4" x 1/2" thru 6" x 4" Page 47</p>	 <p><b>Fig. 383</b> Hex Bushing Size Range: 1 1/2" x 1/4" thru 10" x 8" Page 48 - 49</p>	 <p><b>Fig. 385</b> Face Bushing Size Range: 3" x 2" thru 4" x 3" Page 49</p>	 <p><b>Fig. 387</b> Square Head Plugs, Cored Size Range: 3/4" thru 4" Page 50</p>	 <p><b>Fig. 388</b> Square Head Plugs, Solid Size Range: 1/2" thru 3 1/2" Page 50</p>
 <p><b>Fig. 389</b> Bar Plugs, Cored Size Range: 4" thru 8" Page 50</p>	 <p><b>Fig. 380</b> Bar Plugs, Solid Size Range: 4" thru 8" Page 50</p>	 <p><b>Fig. 390</b> Countersunk Plugs Size Range: 1" thru 4" Page 50</p>	 <p><b>Fig. 381</b> Cap Size Range: 2 1/2" thru 8" Page 50</p>	 <p><b>Fig. 370</b> Locknut Size Range: 2 1/2" thru 4" Page 51</p>	

# PICTORIAL TABLE OF CONTENTS

## Cast Iron *(Continued)*

### CAST IRON THREADED FITTINGS – CLASS 250 (EXTRA HEAVY)

 <p><b>Fig. 421</b> 90° Elbow Size Range: 1/4" thru 3" Page 51</p>	 <p><b>Fig. 424</b> 45° Elbow Size Range: 1/2" thru 2 1/2" Page 51</p>	 <p><b>Fig. 425</b> Tee Size Range: 1/4" thru 4" Page 52</p>	 <p><b>Fig. 426</b> Reducing Tee Size Range: 3/4" x 3/4" x 1/2" thru 2" x 2" x 1 1/2" Page 52</p>
---	---	--	--

### CAST IRON DRAINAGE FITTINGS

 <p><b>Fig. 701</b> 90° Short Turn Elbow Size Range: 1 1/2" thru 4" Page 54</p>	 <p><b>Fig. 701R</b> 90° Reducing Short Turn Elbow Sizes: 1 1/2" x 1 1/4" &amp; 2" x 1 1/2" Page 54</p>	 <p><b>Fig. 702</b> 90° Long Turn Elbow Size Range: 1 1/2" thru 4" Page 54</p>	 <p><b>Fig. 702A</b> 90° Extra Long Turn Elbow Sizes: 1 1/2" &amp; 2" Page 54</p>	 <p><b>Fig. 703</b> 60° Short Turn Elbow Size: 1 1/2" Page 54</p>
 <p><b>Fig. 705</b> 45° Short Turn Elbow Size Range: 1 1/2" thru 4" Page 55</p>	 <p><b>Fig. 706</b> 45° Long Turn Elbow Size: 1 1/2" Page 55</p>	 <p><b>Fig. 707</b> 22 1/2° Elbow Sizes: 1 1/2" &amp; 2" Page 55</p>	 <p><b>Fig. 708</b> 11 1/4° Elbow Sizes: 1 1/2" &amp; 2" Page 55</p>	 <p><b>Fig. 718</b> 90° Street Elbow Sizes: 1 1/2" &amp; 2" Page 57</p>
 <p><b>Fig. 719</b> 45° Street Elbow Sizes: 1 1/2" &amp; 2" Page 57</p>	 <p><b>Fig. 722</b> Tee Sizes: 1 1/2" &amp; 2" Page 57</p>	 <p><b>Fig. 723</b> Reducing Tee Size: 2" x 2" x 1 1/2" Page 57</p>	 <p><b>Fig. 726</b> 90° Short Turn Y-Branch Tee Size Range: 1 1/2" thru 4" Page 58</p>	 <p><b>Fig. 727</b> 90° Reducing Short Turn Y-Branch Tee Sizes: 2" x 2" x 1 1/2" &amp; 2" x 1 1/2" x 1 1/2" Page 58</p>
 <p><b>Fig. 729</b> Reducing Double Short Turn Tee Size: 2" x 1 1/2" Page 58</p>	 <p><b>Fig. 730</b> 90° Long Turn Y-Branch Tee Sizes: 1 1/2" &amp; 2" Page 58</p>	 <p><b>Fig. 731</b> 90° Reducing Long Turn Y-Branch Tee Size: 2" x 2" x 1 1/2" Page 59</p>	 <p><b>Fig. 734</b> 45° Y-Branch Size Range: 1 1/2" thru 4" Page 59</p>	 <p><b>Fig. 735</b> 45° Reducing Y-Branch Sizes: 2" x 2" x 1 1/2" &amp; 4" x 4" x 3" Page 59</p>
 <p><b>Fig. 736</b> 45° Double Y-Branch Size: 1 1/2" Page 59</p>	 <p><b>Fig. 753</b> Coupling Size: 1 1/2" Page 60</p>	 <p><b>Fig. 744</b> Tucker Connection Size Range: 1 1/2" thru 4" Page 60</p>	 <p><b>Fig. 752</b> P-Trap Size Range: 1 1/2" &amp; 3" Page 60</p>	 <p><b>Fig. 754</b> Bath P-Trap Sizes: 1 1/2" &amp; 2" Page 60</p>

## Cast Iron (Continued) – Merchant Steel

### CAST IRON FLANGED FITTINGS – CLASS 125 (STANDARD)

 <p><b>Fig. 801</b> 90° Flanged Elbow Size Range: 1½" thru 12" Page 62</p>	 <p><b>Fig. 802</b> 45° Flanged Elbow Size Range: 2" thru 12" Page 62</p>	 <p><b>Fig. 803</b> 90° Reducing Flanged Elbow Size Range: 2½" x 2" thru 12" x 10" Page 63</p>	 <p><b>Fig. 804</b> 90° Long Radius Flanged Elbow Size Range: 2" thru 10" Page 63</p>	 <p><b>Fig. 805</b> 90° Flanged Base Elbow Sizes: 4" &amp; 6" Page 64</p>
 <p><b>Fig. 811</b> Flanged Tee Size Range: 1½" thru 12" Page 64</p>	 <p><b>Fig. 812</b> Flanged Reducing Tee Size Range: 3" x 3" x 2" thru 12" x 12" x 8" Page 65</p>	 <p><b>Fig. 821</b> Flanged Cross Sizes: 2" thru 8" Page 66</p>	 <p><b>Fig. 823</b> Flanged Lateral Size Range: 3" thru 8" Page 66</p>	 <p><b>Fig. 825</b> Flanged Concentric Reducer Size Range: 2" x 1½" thru 12" x 10" Page 67</p>
 <p><b>Fig. 826</b> Flanged Eccentric Reducer Size Range: 3" x 2" thru 10" x 8" Page 67</p>	<h3>CAST IRON THREADED FITTING</h3> <div style="text-align: center;">  <p><b>Safety Valve Discharge Elbow – Fig. 1538</b> Screwed Cast Iron • Size Range: 2½" thru 4" Page 71</p> </div>			

### IRON FLANGES – CLASS 125 (STANDARD)

 <p><b>Fig. 1011</b> Companion Flange Size Range: ¾" x 3⅞" thru 12" x 19" Page 68</p>	 <p><b>Fig. 1016</b> Reducing Flange Size Range: 1" x 5" thru 8" x 19" Page 69</p>	 <p><b>Fig. 1018</b> Blind Flange Size Range: 1" x 4¼" thru 12" x 19" Page 68</p>
--	---	--

### IRON FLANGES – CLASS 250 (EXTRA HEAVY)

 <p><b>Fig. 1025</b> Companion Flange Size Range: 1¼" x 5¼" thru 8" x 15" Page 70</p>	 <p><b>Fig. 1030</b> Reducing Flange Size Range: 2" x 8¼" thru 4" x 11" Page 70</p>	<p><b>Fig. 1021</b> Blind Flange Size Range: 1½" x 6⅞" thru 8" x 15" Page 70</p>
--	--	--

### MERCHANT STEEL BUSHINGS, CAPS & PLUGS

 <p><b>Hex Bushing</b> Size Range: ¼" x ⅛" thru 1" x ¾" Page 73</p>	 <p><b>Countersunk Plugs</b> (Square and Hex Socket) Size Range: ⅛" thru 2" Page 73</p>	 <p><b>Flush Bushings</b> Size Range: ¼" x ⅛" thru ½" x ⅜" Page 74</p>
 <p><b>Caps</b> Size Range: ⅛" thru ¾" Page 74</p>	 <p><b>Solid Square Head Plugs</b> Size Range: ⅛" thru 2" Page 74</p>	

# PICTORIAL TABLE OF CONTENTS

## Steel Pipe Nipples – Forged Steel

### PIPE NIPPLES – BLACK & GALVANIZED



**Seamless Pipe Nipples**  
Std. Sch. 40, XH Sch. 80, Sch. 160, XXH  
Size Range: 1/8" thru 6"  
Page 76



**Welded Pipe Nipples**  
Std. Sch. 40, XH Sch. 80  
Size Range: 1/8" thru 6"  
Page 77 - 79

**Special Design Pipe Nipples**  
Page 80 - 81

### STEEL PIPE COUPLINGS



**Fig. 336**  
Standard, Full & Half  
Size Range: 1/8" thru 6"  
Page 82



**Fig. 337**  
Extra Strong(XS), Full & Half  
Size Range: 1/8" thru 6"  
Page 83



**Fig. 346**  
Standard, Right & Left  
Size Range: 1/2" thru 2"  
Page 84



**Fig. 347**  
Extra Strong (XS), Right & Left  
Size Range: 1/2" thru 2"  
Page 84



**Fig. 348**  
API Line Pipe Coupling  
Size Range: 1/8" thru 12"  
Page 85



**Fig. 349**  
Water Well Reamed & Drifted Coupling  
Size Range: 1/4" thru 12"  
Page 86



**Fig. 350**  
#9 Drive Coupling  
Size Range: 1/4" thru 2"  
Page 86



**Fig. 379**  
Shallow Well Coupling  
Size Range: 1/4" thru 2"  
Page 86

### FORGED STEEL FITTINGS – CLASS 2000 THREADED



**Fig. 2101**  
90° Elbow  
Size Range: 1/4" thru 4"  
Page 88



**Fig. 2102**  
45° Elbow  
Size Range: 1/4" thru 3"  
Page 88



**Fig. 2103**  
Tee  
Size Range: 1/4" thru 4"  
Page 89



**Fig. 2104**  
Cross  
Size Range: 1/4" thru 3"  
Page 89

### FORGED STEEL FITTINGS – HIGH PRESSURE PLUGS & BUSHINGS



**Fig. 2122**  
Square Head Plug  
Size Range: 1/8" thru 4"  
Page 107



**Fig. 2142**  
Hex Head Plug  
Size Range: 1/8" thru 4"  
Page 107



**Fig. 2121**  
Round Head Plug  
Size Range: 1/8" thru 4"  
Page 107



**Fig. 2139**  
Hex Head Bushing  
Size Range: 1/4" x 1/8" thru 4" x 1/2"  
Page 108



**Fig. 2140**  
Flush Bushing  
Size Range: 1/4" x 1/8" thru 2" x 1/4"  
Page 108

# PICTORIAL TABLE OF CONTENTS

## Forged Steel *(Continued)*

### FORGED STEEL FITTINGS – CLASS 3000 THREADED

 <p><b>Fig. 2111</b> 90° Elbow Size Range: 1/8" thru 4" Page 90</p>	 <p><b>Fig. 2112</b> 45° Elbow Size Range: 1/8" thru 4" Page 90</p>	 <p><b>Fig. 2114</b> Tee Size Range: 1/8" thru 4" Page 90</p>	 <p><b>Fig. 2115</b> Cross Size Range: 1/8" thru 4" Page 91</p>	 <p><b>Fig. 2113</b> 90° Street Elbow Size Range: 1/8" thru 2" Page 91</p>
 <p><b>Fig. 2116</b> Lateral Size Range: 1/2" thru 2" Page 91</p>	 <p><b>Fig. 2117</b> Coupling Size Range: 1/8" thru 4" Page 92</p>	 <p><b>Fig. 2119</b> Half Coupling Size Range: 1/8" thru 4" Page 92</p>	 <p><b>Fig. 2118</b> Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 1 1/2" Page 93</p>	 <p><b>Fig. 2120</b> Pipe Cap Size Range: 1/8" thru 4" Page 93</p>

### FORGED STEEL FITTINGS – CLASS 6000 THREADED

 <p><b>Fig. 2131</b> 90° Elbow Size Range: 1/8" thru 4" Page 94</p>	 <p><b>Fig. 2132</b> 45° Elbow Size Range: 1/8" thru 4" Page 94</p>	 <p><b>Fig. 2134</b> Tee Size Range: 1/8" thru 4" Page 94</p>	 <p><b>Fig. 2135</b> Cross Size Range: 1/8" thru 4" Page 95</p>	 <p><b>Fig. 2133</b> 90° Street Elbow Size Range: 1/8" thru 1 1/2" Page 95</p>
 <p><b>Fig. 2136</b> Lateral Size Range: 1/2" thru 1 1/2" Page 95</p>	 <p><b>Fig. 2137</b> Coupling Size Range: 1/8" thru 4" Page 96</p>	 <p><b>Fig. 2141</b> Half Coupling Size Range: 1/8" thru 4" Page 96</p>	 <p><b>Fig. 2138</b> Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 2" Page 97</p>	 <p><b>Fig. 2143</b> Pipe Cap Size Range: 1/8" thru 4" Page 97</p>

### FORGED STEEL UNIONS

Class 3000		Class 6000	
 <p><b>Fig. 2125</b> Threaded Union Size Range: 1/4" thru 3" Page 111</p>	 <p><b>Fig. 2126</b> Socket Weld Union Size Range: 1/4" thru 3" Page 111</p>	<p><b>Fig. 2127</b> Threaded Union Size Range: 1/4" thru 2" Page 112</p>	<p><b>Fig. 2128</b> Socket Weld Union Size Range: 1/4" thru 2" Page 112</p>

### FORGED STEEL FITTINGS SOCKET WELD REDUCER INSERTS

<p><b>Class 3000</b> For use with Sch. 40 &amp; 80 Pipe Size Range: 1/2" x 1/4" thru 3" x 2 1/2" Page 109</p>	<p><b>Class 6000</b> For use with Sch. 160 Pipe Size Range: 3/4" x 1/4" thru 2" x 1 1/4" Page 110</p>
---	---

# PICTORIAL TABLE OF CONTENTS

## Forged Steel *(Continued)* – Anvilets

### FORGED STEEL FITTINGS CLASS 3000 SOCKET WELD

 <b>Fig. 2150</b> 90° Elbow Size Range: 1/8" thru 4" Page 98	 <b>Fig. 2151</b> 45° Elbow Size Range: 1/8" thru 4" Page 98	 <b>Fig. 2152</b> Tee Size Range: 1/8" thru 4" Page 99
 <b>Fig. 2153</b> Cross Size Range: 1/8" thru 4" Page 99	 <b>Fig. 2158</b> Lateral Size Range: 1/2" thru 2" Page 100	 <b>Fig. 2154</b> Coupling Size Range: 1/8" thru 4" Page 100
 <b>Fig. 2155</b> Half Coupling Size Range: 1/8" thru 4" Page 101	 <b>Fig. 2156</b> Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 2" Page 101	 <b>Fig. 2157</b> Pipe Cap Size Range: 1/8" thru 4" Page 102

### FORGED STEEL FITTINGS CLASS 6000 SOCKET WELD

 <b>Fig. 2170</b> 90° Elbow Size Range: 1/2" thru 4" Page 103	 <b>Fig. 2171</b> 45° Elbow Size Range: 1/2" thru 4" Page 103	 <b>Fig. 2172</b> Tee Size Range: 1/2" thru 4" Page 104
 <b>Fig. 2173</b> Cross Size Range: 1/2" thru 2" Page 104	 <b>Fig. 2178</b> Lateral Size Range: 1/2" thru 1 1/2" Page 104	 <b>Fig. 2174</b> Coupling Size Range: 1/2" thru 4" Page 105
 <b>Fig. 2175</b> Half Coupling Size Range: 1/2" thru 4" Page 105	 <b>Fig. 2176</b> Reducing Coupling Size Range: 1/2" x 1/4" thru 4" x 2" Page 106	 <b>Fig. 2177</b> Pipe Cap Size Range: 1/2" thru 4" Page 106

### UNIVERSAL ELBOWLET LATERAL ANVILET

 <b>Class 3000 &amp; 6000 Buttweld, Threaded &amp; Socket-Weld</b> Class 3000 Threaded & Socket-Weld/Standard & XS/XH Buttweld Size Range: 1/2" thru 2" Class 6000 Threaded & Socket-Weld Size Range: 1/2" thru 1 1/2" Page 119	 <b>Class 3000 Buttweld &amp; Threaded</b> Class 3000 Standard/XS Butt Weld Size Range: 1/2" thru 2" Class 3000 Threaded/Standard Size Range: 1/2" thru 2" Page 120
---	--

### FLAT ANVILET

**Class 3000 Threaded, Buttweld & Socket-Weld**  
Size Range: 1/4" thru 3"  
Page 121

### UNIVERSAL FORGED STEEL ANVILETS

Buttweld			
 Standard Size Range: 1/8" thru 24" Page 114	 Extra Strong Size Range: 1/8" thru 24" Page 114	 XXS, Sch. 160 Size Range: 1/2" thru 4" Page 115	
Threaded		Socket-Weld	
 Class 3000 Size Range: 1/8" thru 4" Page 116	 Class 6000 Size Range: 1/2" thru 2" Page 116	 Class 3000 Size Range: 1/8" thru 4" Page 117	 Class 6000 Size Range: 1/2" thru 2" Page 117

## Catawissa – J.B. Smith

### CATAWISSA HAMMER UNIONS

				
<p><b>Fig. 100</b> Threaded Ends 1,000 psi cwp - 1,500 psi test Size Range: 2" thru 6" Page 123</p>	<p><b>Fig. 100</b> 8Rd EUE Threaded Ends 1,000 psi cwp - 1,500 psi test Size: 2" Page 123</p>	<p><b>Fig. 200</b> Threaded Ends 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 4" Page 124</p>	<p><b>Fig. 206</b> Threaded Ends 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 6" Page 125</p>	
				
<p><b>Fig. 211</b> Threaded Ends Insulating Union 2,000 psi cwp - 3,000 psi test Sizes: 1" &amp; 2" Page 126</p>	<p><b>Fig. 300</b> Flat-Face Union 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 4" Page 127</p>	<p><b>Fig. 301</b> Steam Service Union 3,000 psi cwp - 4,500 psi test Size Range: 1" &amp; 2" Page 128</p>	<p><b>Fig. 400</b> Threaded Ends 4,000 psi cwp - 6,000 psi test Size Range: 2" thru 4" Page 128</p>	<p><b>Fig. 602</b> Threaded Ends 6,000 psi cwp - 9,000 psi test Size Range: 1" thru 3" Page 129</p>
<p><b>Fig. 602</b> Buttweld Ends - Sch. XXH 6,000 psi cwp - 9,000 psi test Size: 3" Page 129</p>			<p><b>Fig. 1502</b> Buttweld Ends - Sch. XXH 15,000 psi cwp - 22,500 psi test Sizes: 2" &amp; 3" Page 131</p>	
	<p><b>Fig. 607</b> Threaded Ends Well Service Union 2,000 psi cwp - 3,000 psi test Sizes: 1 1/2" &amp; 2" Page 130</p>	<p><b>Fig. 1502</b> Threaded Ends 15,000 psi cwp - 22,500 psi test Sizes: 2" &amp; 3" Page 131</p>		

### J.B. SMITH

						
<p><b>Concentric Swage Nipple</b> Size Range: 1/4" x 1/8" thru 1" x 3/4" Page 136</p>	<p><b>Concentric Swage Nipple</b> Size Range: 1 1/4" x 1/4" thru 8" x 6" Page 137</p>	<p><b>Eccentric Swage Nipple</b> Size Range: 1/4" x 1/8" thru 4" x 3 1/2" Page 138</p>	<p><b>Stainless &amp; Alloy Steel Swage Nipple</b> Size Range: 1/4" x 1/8" thru 4" x 3 1/2" Page 139</p>	<p><b>Carbon Steel Bull Plug</b> Size Range: 1/8" thru 8" Page 140</p>	<p><b>Solid Refinery Plug</b> Black (non-plated) Carbon Steel Size Range: 1/8" thru 2" Page 140</p>	<p><b>Adapter Nipples</b> Size Range: 3/4" thru 12" Page 141</p>

# PICTORIAL TABLE OF CONTENTS

## J.B.S. Oil Country Products – Oil Country Fittings

### J.B.S. OIL COUNTRY PRODUCTS

 <p><b>Swage Nipple</b> (Oil Country Sizes) Large End Upset Reduced to Regular or Upset Size Range: 1" x 3/4" thru 4" x 3 1/2" Page 143</p>	 <p><b>Swage Nipple</b> (Oil Country Sizes) Large End Non-Upset Reduced to Upset Size Range: 1" x 3/4" thru 4" x 3" Page 143</p>	 <p><b>Swage Nipple</b> Oil Country Tubing &amp; Casing non EUE ends Page 144</p>	 <p><b>Tubing Bull Plugs</b> Size Range: 3/4" EUE thru 3" EUE Page 145</p>	 <p><b>Casing Bull Plugs</b> Size Range: 4 1/2" thru 10 3/4" Page 145</p>	 <p><b>API Bull Plug Female</b> Size Range: 3/4" thru 4" EUE Page 145</p>
 <p><b>Bell Nipple</b> Size Range: 4 1/2" thru 8 5/8" Page 146</p>	 <p><b>Tubing Nipple</b> Standard Weight Size Range: 1" thru 4" Page 146</p>	 <p><b>Tubing Nipple</b> Extra Heavy Weight Size Range: 1" thru 4" Page 146</p>	 <p><b>Oil Country Casing Nipple</b> Size Range: 4 1/2" thru 16" Page 147</p>	 <p><b>API Casing Coupling</b> Short Thread Size Range: 4 1/2" thru 20" Page 148</p>	 <p><b>API Casing Coupling</b> Long Thread Size Range: 4 1/2" thru 13 3/8" Page 148</p>
 <p><b>Combination Coupling J-55</b> Size Range: 2" thru 4" Page 148</p>	 <p><b>Sub Tubing Coupling J-55</b> Size Range: 2" EUE x 2" Reg thru 4" EUE x 4" Reg Page 149</p>	 <p><b>API Tubing Coupling</b> Size Range: 2" thru 4" Page 149</p>	 <p><b>Special Clearance Tubing Coupling</b> Size Range: 2" thru 3" Page 149</p>	 <p><b>Chambers/Pressure Vessels</b> Size Range: 2" thru 8" Page 150</p>	

### OIL COUNTRY FITTING



**Pumping Tee**

Size Range:

2" 8RD EUE x 2" 8RD EUE x 2" 11 1/2" REG thru 3" 8RD EUE x 3" 8RD EUE x 3" 8V LP  
Page 151