

Rigid and IMC Fittings

Reducing Bushings

Used to reduce the entry size of a run of threaded conduit.

Standard Materials/Finishes

- Steel for small size and Malleable Iron for big size
- Zinc Plated

Compliances and Certifications

- UL File No.E307843
- UL514B



Steel	Catalog Number		Dimensions			
	Steel	Trade Size	A		B	
			Inch	mm	Inch	mm
	1160	1/2" -3/8"	0.81	20.6	0.49	12.4
	1161	3/4" -1/2"	1.04	26.4	0.57	14.5
	1162	1" -1/2"	1.28	32.5	0.64	16.3
	1163	1" -3/4"	1.28	32.5	0.64	16.3
	1164	1 1/4" -1/2"	1.63	41.4	0.69	17.5
	1165	1 1/4" -3/4"	1.63	41.4	0.69	17.5
	1166	1 1/4" -1"	1.63	41.4	0.69	17.5
	1167	1 1/2" -1/2"	1.86	47.2	0.75	19.1
	1168	1 1/2" -3/4"	1.86	47.2	0.75	19.1
	1169	1 1/2" -1"	1.86	47.2	0.75	19.1
	1170	1 1/2" -1 1/4"	1.86	47.2	0.75	19.1
	1171	2" -1/2"	2.33	59.2	0.82	20.8
	1172	2" -3/4"	2.33	59.2	0.82	20.8
	1173	2" -1"	2.33	59.2	0.82	20.8
	1174	2" -1 1/4"	2.33	59.2	0.82	20.8
	1175	2" -1 1/2"	2.33	59.2	0.82	20.8



Malleable Iron	Malleable Iron		A		B	
	Malleable Iron	Trade Size	Inch		mm	
			Inch	mm	Inch	mm
	RB-250100M	2 1/2" -1"	2.88	73.2	1.30	33.0
	RB-250125M	2 1/2" -1 1/4"	2.88	73.2	1.30	33.0
	RB-250150M	2 1/2" -1 1/2"	2.88	73.2	1.30	33.0
	RB-250200M	2 1/2" -2"	2.88	73.2	1.30	33.0
	RB-300125M	3" -1 1/4"	3.50	88.9	1.54	39.1
	RB-300150M	3" -1 1/2"	3.50	88.9	1.54	39.1
	RB-300200M	3" -2"	3.50	88.9	1.54	39.1
	RB-300250M	3" -2 1/2"	3.50	88.9	1.54	39.1
	RB-350150M	3 1/2" -1 1/2"	4.00	101.6	1.59	40.4
	RB-350200M	3 1/2" -2"	4.00	101.6	1.59	40.4
	RB-350250M	3 1/2" -2 1/2"	4.00	101.6	1.59	40.4
	RB-350300M	3 1/2" -3"	4.00	101.6	1.59	40.4
	RB-400200M	4" -2"	4.51	114.6	1.77	45.0
	RB-400250M	4" -2 1/2"	4.51	114.6	1.77	45.0
	RB-400300M	4" -3"	4.51	114.6	1.77	45.0
	RB-400350M	4" -3 1/2"	4.51	114.6	1.77	45.0

