

Schedule 80 Rigid PVC Conduit

PART NUMBER	SIZE	OD		MIN AVERAGE ID		MIN T	
		AVERAGE		SCHEDULE 80		SCHEDULE 80	
		INCHES	MM	INCHES	MM	INCHES	MM
DIC80-050	1/2	0.840±0.004	21.34±0.10	0.502	12.75	0.147	3.73
DIC80-075	3/4	1.050±0.004	26.67±0.10	0.698	17.72	0.154	3.91
DIC80-100	1	1.315±0.005	33.40±0.13	0.910	23.11	0.179	4.55
DIC80-125	1-1/4	1.660±0.005	42.16±0.13	1.227	31.16	0.191	4.85
DIC80-150	1-1/2	1.900±0.006	48.26±0.15	1.446	36.72	0.200	5.08
DIC80-200	2	2.375±0.006	60.32±0.15	1.881	47.77	0.218	5.54
DIC80-250	2-1/2	2.875±0.007	73.02±0.18	2.250	57.15	0.276	7.01
DIC80-300	3	3.500±0.008	88.90±0.20	2.820	71.62	0.300	7.62
DIC80-350	3-1/2	4.000±0.008	101.60±0.20	3.280	83.31	0.318	8.08
DIC80-400	4	4.500±0.009	114.30±0.23	3.737	94.91	0.337	8.56
DIC80-500	5	5.563±0.010	141.30±0.25	4.713	119.71	0.375	9.53
DIC80-600	6	6.625±0.011	168.28±0.28	5.646	143.41	0.432	10.97
DIC80-800	8	8.625±0.011	219.07±0.28	7.513	190.83	0.500	12.70



Properties:

- PVC material test: ASTM D1784-20
- UL651 Standard.
- Comply with NEMA TC-2.
- PVC material with great corrosion resistant.
- Impact resistant.
- Self extinguishing, fire retardant.
- Smooth interior and outside.
- Suitable for underground or above ground applications.
- Standard lengths 10/20ft with a belled end or not. Other lengths can be customized for specific applications
- FT4 rated.

