

# Rigid and IMC Fittings

## Grounding Hubs-Malleable Iron

THG-M Series Conduit Hubs are used to terminate electrical conduit through the walls of enclosure, indoors and outdoors application specifically for food plants, distilleries, breweries, sewage disposal plants, chemical plants, paper processing mills and refineries

### Standard Materials/Finishes

- Body/Gland Nut: Malleable Iron/Zinc Plate
- Screw: Steel/Zinc Plated
- Insulator: Thermoplastics

### Compliances and Certifications

- UL File No.E317578
- UL-514B & UL-467
- suitable for Class I, Division 2; Class II, Divisions 1 & 2 and Class III, Divisions 1 & 2 when installed in accordance with the NEC 501-4(B), 501.10(B)(4), 502-4(A)(2), 503-3(A)

Catalog Number	Trade Size	Dimensions		
		A Inch mm	B Inch mm	C Inch mm
THG-50M	1/2"	1.54 39.1	1.54 39.1	1.54 39.1
THG-75M	3/4"	1.77 45.0	1.77 45.0	1.77 45.0
THG-100M	1"	2.15 54.6	2.15 54.6	2.15 54.6
THG-125M	1-1/4"	2.50 63.5	2.50 63.5	2.50 63.5
THG-150M	1-1/2"	3.00 76.2	3.00 76.2	3.00 76.2
THG-200M	2"	3.35 85.1	3.35 85.1	3.35 85.1
THG-250M	2-1/2"	3.92 99.6	3.92 99.6	3.92 99.6
THG-300M	3"	4.74 120.4	4.74 120.4	4.74 120.4
THG-350M	3-1/2"	5.39 136.9	5.39 136.9	5.39 136.9
THG-400M	4"	5.91 150.1	5.91 150.1	5.91 150.1
THG-500M	5"	7.36 186.9	3.46 87.9	6.10 154.9
THG-600M	6"	8.39 213.1	3.62 91.9	7.25 184.2

