

Reducing Couplings

Reducing Coupling

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Steel: Sizes available are ¾" to ½" to 3"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½"- 2". For sizes 2-½" - 2-½" - 5", the length of the sleeve extension(s) shall be at least 2"
- Sealing sleeves extender 1 pipe diameter or 2 inches, whichever is greater, beyond all female openings

Standards:

- National Electric Code/ CEC
 - REC 21 - 01210
 - Class I, Division 1 & 2, Groups A, B, C, D
 - Class III
- UL Standard: 886
- CSA Standard: C22.2 No. 30



Applications:

Calbond Reducing Couplings are used to join conduit and fittings of different sizes. They are provided with different size sleeves to match the fittings thread sizes.

Part Number	Trade Size (in)	Weight per 100 (Lb)
PV0700REC21	¾ - ½	20
PV1000REC31	1 - ½	70
PV1000REC32	1 - ¾	50
PV1200REC42	1¼ - ¾	100
PV1200REC43	1¼ - 1	80
PV1500REC52	1½ - ¾	140
PV1500REC53	1½ - 1	120
PV1500REC54	1½ - 1¼	130
PV2000REC602	2 - ¾	150
PV2000REC603	2 - 1	230
PV2000REC604	2 - 1¼	260
PV2000REC605	2 - 1½	280
PV2500REC75	2½ - 1½	320
PV3000REC86	3 - 2	370
PV3500REC97	3½ - 2½	460
PV4000REC108	4 - 3	590
PV5000REC01210	5 - 4	740

All dimensions are for informational purposes only *Tolerances +/- 5%

