Y35

12-Ton, C-Head, HYPRESS™
Hydraulic Self-Contained, Hand Operated Tool

- 180° head rotation
- Uses BURNDY U style dies (sold separately)
- Body and handles rubber covered for impact protection
- Trigger controlled ram release



For Use On:

Copper #8 str. - 500 kcmil code cable
Grounding Terminals:
YGH, YGHA, YGF
Grounding Splices:
YGS, YGHS

Copper #8 str. - 500 kcmil and up to 3/4" ground rod
Grounding Taps:
YGHC-C, YGHP-C, YGHR-C

Copper #8 str. - 750 kcmil code cable, N30 - N500 Navy cable, flexible, and extra flex
Terminals (Bare):
YA, YA-2N, YA-L, YA-LB, YA-2LN
Terminals (Insulated):
YAEV-L, YAEV-H, YAEV-RS, YAEV-RH
Splices to 400 kcmil only:
YS, YS-T, YS-L, YS-LB, YSV-L, YSM

Aluminum #8 str. - 750 kcmil code cable
Terminals:
YA-A, AYP, AYPO
Splices to 350 kcmil only:
YSA, YRB, YS-AT

ACSR:
See Overhead Transmission and Distribution sections in the BURNDY Master Catalog

Specifications:

Output Force:	12 Tons
Tool Weight:	13.0 lbs
Size:	23.25" x 8.75" x 4.75"
Die Style:	U style
Warranty:	5 year limited warranty

Variations:

Catalog Number:	Description:
Y35	Standard tool (rubber covered body and handles only)
Y352	Y35 with rubber covered head, body, and handles

Accessories:

Catalog Number:	Description:
PT2972:	Steel Carry Case for Y35 (included with tool)
PT29360:	Steel Carry Case for Y352 (included with tool)
Y35/Y39REPKITA:	Seal Repair Kit

Canada: 1-800-387-6487 www.burndy.com US: 1-800-346-4175

+51 991 872 290

Siguenos en nuestras redes

Escanea el QR
Visita nuestro Catalogo