# PATRIOT® 12 Ton, C-Head
## Hydraulic Self-Contained, 18V Lithium-Ion



## Tool Series: PAT750

- 1.65" jaw opening
- Used with U dies
- C-head with 355° head rotation
- Patented T-Track alignment guide for HYGROUND® as well as other asymmetrical connectors
- Includes 2 batteries, charger, and case
- **EP Enhanced Power** — tools accept 2.0, 3.0, 4.0, 5.0, and 6.0Ah Makita batteries

## For Use On:

| | | |
|---|---|---|
| **Tension Sleeves** | | |
| | Copper | #8 sol. - 500 kcmil |
| | Aluminum | #8 sol. - 587.2 kcmil |
| | ACSR | #4 - 556.5 kcmil |
| **Taps** | | |
| | Copper | #14 sol. - 500 kcmil |
| | Aluminum | #8 - 500 kcmil |
| **Aerial Cable** | | |
| | Copper | #6 - 500 kcmil |
| **Terminals & Splices** | | |
| | Copper | #8 - 750 kcmil |
| | Aluminum | #8 - 750 kcmil |
| | ACSR | #4 - 556 kcmil |
| **HYGROUND® (Compression Grounding)** | | |
| | Copper | #8 - 500 kcmil |
| | Ground Rods | 1/2" - 1" diameter |

## Models:

| | |
|---|---|
| PAT750LI | with 3.0Ah Li-Ion batteries, hard case |
| PAT750CLI | with rubber covered head (3.0Ah), hard case |
| PAT750L5 | with 5.0Ah Li-Ion batteries, hard case |
| PAT750CL5 | with rubber covered head (5.0Ah), hard case |
| PAT750LIPB | with 3.0Ah Li-Ion batteries, pro bag |
| PAT750CLIPB | with rubber covered head (3.0Ah), pro bag |
| PAT750L5PB | with 5.0Ah Li-Ion batteries, pro bag |
| PAT750CL5PB | with rubber covered head (5.0Ah), pro bag |

## Specifications:

| | |
|---|---|
| **Output Force:** | 12 Tons |
| **Tool Weight:** | 14.25 lbs (without battery) |
| **Size:** | 15.75" x 13.50" x 3.50" |
| **Die Style:** | U |
| **Jaw Opening:** | 1.65" |
| **Operating Voltage:** | 18 V-DC Lithium-Ion |
| **Recharge Time:** | 30 minutes (3.0Ah)<br>45 minutes (5.0Ah) |
| **Warranty:** | 5 year limited warranty<br>Lifetime warranty on INFINITY DRIVE®<br>3 year on batteries and charger |



*Wide U-dies (sold separately) can be used with long barrel terminals and splices saving time and labor!*

## Accessories:

| | |
|---|---|
| **BAT18VLI:** | 3.0Ah Li-Ion battery |
| **BAT18V5AHLI:** | 5.0Ah Li-Ion battery |
| **PATCHGRLI:** | 120V-AC Charger |
| **PATCHGRLIDC:** | 12/24V-DC Charger |
| **PT208620:** | Lanyard |
| **FORCEGAUGE1215:** | Force Test Gauge |