Rigid and IMC Fittings

Grounding Hubs-Malleable Iron

THG-M Series Conduit Hubs are used to terminate electrical conduit through the walls of enclosure, indoors and outdoors application specifically for food plants, distilleries, breweries, sewage disposal plants, chemical plants, paper processing mills and refineries

Standard Materials/Finishes

- Body/Gland Nut: Malleable Iron/Zinc Plated
- Screw: Steel/Zinc Plated
- Insulator: Thermoplastics

Compliances and Certifications

- UL File No.E317578
- UL-514B & UL-467
- suitable for Class I, Division 2; Class II, Divisions 1 & 2 and Class III, Divisions 1 & 2 when installed in accordance with the NEC 501-4(B), 501.10(B)(4), 502-4(A)(2), 503-3(A)





Catalog Number	Trade Size	Dimensions A Inch	A mm	B Inch	B mm	C Inch	C mm
THG-50M	1/2"	1.54	39.1	1.54	39.1	1.54	39.1
THG-75M	3/4"	1.77	45.0	1.77	45.0	1.77	45.0
THG-100M	1"	2.15	54.6	2.15	54.6	2.15	54.6
THG-125M	1-1/4"	2.50	63.5	2.50	63.5	2.50	63.5
THG-150M	1-1/2"	3.00	76.2	3.00	76.2	3.00	76.2
THG-200M	2"	3.35	85.1	3.35	85.1	3.35	85.1
THG-250M	2-1/2"	3.92	99.6	3.92	99.6	3.92	99.6
THG-300M	3"	4.74	120.4	4.74	120.4	4.74	120.4
THG-350M	3-1/2"	5.39	136.9	5.39	136.9	5.39	136.9
THG-400M	4"	5.91	150.1	5.91	150.1	5.91	150.1
THG-500M	5"	7.36	186.9	3.46	87.9	6.10	154.9
THG-600M	6"	8.39	213.1	3.62	91.9	7.25	184.2