Tooling
Crimpers — Self-Contained Hydraulic

Y500CTHS



6-Ton, Latch Head, L'IL CRIMP™
Hydraulic Self-Contained, Hand Operated Tool

- Permanent functional D3 groove (no die needed)
- Used with W, X, and W-VT style dies
- 180° head rotation
- Enhanced clearance for tap connectors

For Use On:

Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid conductors

Installs Splices, Taps or Terminations:
#8 - 600 kcmil Copper Str.
#8 - 350 kcmil Flex
#8 - 350 kcmil Aluminum

Specifications:

Output Force:	6 Tons
Tool Weight:	7.8 lbs
Size:	17.63" x 6.00" x 2.68"
Die Style:	W, W-VT and X styles
Warranty:	5 year limited warranty



***WDC4500** range taking die for #4 - 500 Cu Str. and #2 - 4/0 Cu Flex (sold separately)*

Variations:

Catalog Number:	Description:
Y500CTHS	Standard Latch Head Tool

Accessories:

Catalog Number:	Description:
WDC4500:	Range taking die for #4 - 500 Cu Str. and #2 - 4/0 Cu Flex
WDA8300:	Range taking die for #8 - 300 Al, #6 - 400 Cu Str. and #2 - 4/0 Cu Flex
PT212851:	Metal Carrying Case (included with tool)



***WDA8300** range taking die for #8 - 300 Al, #6 - 400 Cu Str. and #2 - 4/0 Cu Flex (sold separately)*

When used with UL Listed/CSA Certified YA, YS, YA-A, and YS-A series terminals and splices, connections are UL/CSA.

Range taking dies also for use on the YAV and YSV series.

US: 1-800-346-4175 www.burndy.com Canada: 1-800-387-6487

+51 991 872 290

Siguenos en nuestras redes

Escanea el QR
Visita nuestro Catalogo