Hot Dip Galvanized Products

ORS Series One hole strap - HDG

Used to support rigid conduit and IMC, liquid tight flexible metallic conduit and liquid tight nonmetallic conduit (type B) to mounting surface.

Malleable Iron/hot dip galvanized

- UL File No.E317579
- UL 2239

ORS-M One hole strap-Malleable Iron





Catalog Number	Trade Size	Dimensions A Inch	A mm	B Inch	B mm	C Inch	C mm
ORS-50M-HDG	1/2"	1.98	50.3	0.67	17.0	0.97	24.6
ORS-75M-HDG	3/4"	2.37	60.2	0.76	19.3	1.1	27.9
ORS-100M-HDG	1"	2.90	73.7	0.82	20.8	1.44	36.6
ORS-125M-HDG	1-1/4"	3.12	79.2	0.82	20.8	1.77	45.0
ORS-150M-HDG	1-1/2"	3.90	99.1	1.05	26.7	2.06	52.3
ORS-200M-HDG	2"	4.77	121.2	1.36	34.5	2.59	65.8
ORS-250M-HDG	2-1/2"	5.45	138.4	1.36	34.5	3.05	77.5
ORS-300M-HDG	3"	6.74	171.2	1.54	39.1	3.77	95.8
ORS-350M-HDG	3-1/2"	7.72	196.1	1.91	48.5	4.24	107.7
ORS-400M-HDG	4"	8.13	206.5	2.07	52.6	4.98	126.5
ORS-500M-HDG	5"	10.94	277.9	2.55	64.8	6.22	158.0
ORS-600M-HDG	6"	12.71	322.8	2.91	73.9	7.45	189.2

Hot Dip Galvanized