



TYPE YS

HYLINK™ SPLICE -
LONG BARRELCOPPER COMPRESSION
SPLICEUL Listed 90° C,
600 Volts to 35 kV ◆

C-83

Features and Benefits

- Long barrel length.
 - ◆ Ideal for 600 volt heavy duty applications. Also may be used at higher voltages up to 35KV.
- Four (4) center conductor stops.
 - ◆ Provides a center wire stop for proper conductor insertion.
- High pull out force.
 - ◆ Provides added security for much greater mechanical and electrical properties.

Catalog Number	Conductor		Dimensions		Dieless (# of crimps)	Installation Tooling ▲						Wire Strip Length
	AWG	***	L	B		Mechanical		Y35 ■, Y39, Y750, Y46*		▲		
		MM²				Y1MRTC Y2MR	MD7-34R	MD6 OUR840	Die Number (# crimps)	Color Code	Die Index & Embossment	
YS8C	8 str.	10	1.75	.78	Y81KFT (1) Y81KFTMBH (1) PAT81KFT-18V (1)	Y1MRTC (2)	W8CVT (2)	X8CRT (2)	U8CRT (2)	Red	49	7/8"
YS6C	6 str.	—	2.38	1.09			W5CVT (2)	X5CRT (2)	U5CRT (2)	Blue	7 or 374	1-3/16"
YS5C	5 str.	16	2.55	1.09		Y1MRTC (4)	W4CVT (2)	X4CRT (2)	U4CRT (2)	Gray	8 or 346	1-3/16"
YS4C	4 str.	—	2.55	1.09	Y81KFT (2) Y81KFTMBH (2) PAT81KFT-18V (2)	Y1MRTC (4)	—	U3CRT (2)	—	White	9	1-5/16"
YS3C	3 str./2 sol.	25	2.80	1.22		Y1MRTC (4)	W2CVT/W2CRT	W2CVT/W2CRT	U2CRT (2)	Brown	10	1-5/8"
YR2C2WT	2 str. - 2 sol.	25	2.90	1.44			W2CVT (2)	X2CRT (2)	U2CRT (2)	Brown	10	1-5/16"
YS2C	2 str.	35	2.82	1.22		Y1MRTC (4)	W1CRT (2)	X1CRT (2)	U1CRT-1 (2)	Green	11 or 375	1-7/16"
YS1C	1 str.	50	3.07	1.34			W25VT (4)	X25RT (4)	U25RT (2)	Pink	12 or 348	1-7/16"
YS25	1/0 str.	—	3.06	1.34		—	W26VT (4)	X26RT (4)	U26RT (2)	Black	13	1-9/16"
YS26	2/0 str.	70	3.30	1.45			W27VT (4)	X27RT (4)	U27RT (2)	Orange	14	1-9/16"
YS27	3/0 str.	—	3.30	1.45			W28VT (4)	X28RT (4)	U28RT (2)	Purple	15	1-11/16"
YS28	4/0 str.	—	3.57	1.58			W29VT (4)	—	U29RT (2)	Yellow	16	1-11/16"
YS29	250 kcmil	120	3.58	1.58			W30VT (4)		U30RT (4)	White	17 or 298	2-1/16"
YS30	300 kcmil	150	4.34	1.95			W31VT (4)		U31RT (4)	Red	18 or 324	2-1/16"
YS31	350 kcmil	185	4.35	1.95			W32VT (4)		U32RT (4)	Blue	19 or 470	2-3/16"
YS32	400 kcmil	—	4.62	2.08			W34VT (4)	—	U34RT (4)	Brown	20 or 299	2-5/16"
YS34	500 kcmil	240	4.91	2.20			—		U36RT (4)	Green	22 or 472	2-3/4"
YS36	600 kcmil	300	5.85	2.63					—	U39RT (4)	Black	24
YS39	750 kcmil	—	6.38	2.81	P44RT** (2)					White	27	3-1/16"
YS44	1000 kcmil	500	6.95	2.94	—		—	P46RT** (6)	Green	31	3-1/4"	
YS46	1500 kcmil	—	7.01	3.13				—	—	L48RT (4)	Brown	34
YS48	2000 kcmil	—	7.57	3.27	—	—	—			—	—	—

① Not color coded.

* Use PUADP-1 adapter with U dies in Y46 HYPRESS™.

** P44RT for use with Y46 HYPRESS™ only. PUADP-1 adapter not required.

*** The MM² conductor sizes listed are the recommendations for Class 2 conductor.

■ The maximum size for the Y35 is 400 kcmil.

▲ See tooling section of this catalog for complete tool and die listings.

◆ For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions.

† Requires Y60BU HYPRESS™ with L48RT die set.

Note: All dimensions shown are for reference only.

Blue highlighted items are industry standard and most frequently ordered.