OVERHEAD DISTRIBUTION - COMPRESSION SPLICES

Single Sleeve Full Tension HYSPLICE™ Types YDS-A, YDS-AT

HYSPLICE™ Single Sleeve, Types YDS-A, YDS-AT for AAC (Stranded, Compressed, Compact)

Material: Aluminum

Tension Rating: ANSI C119.4 Class 1 (Full Tension)



Full Tension HYSPLICE™ sleeve made of aluminum tubing with staked-in cable stop. Sizes 1/0 and large tapered for gradual transition of stress. Installed with standard tools and dies. Prefilled with PENETROX™ joint compound, stripsealed, and capped to limit oxide growth and increase connection life.

Catalog Number	Conductor	L	Die Index	Tool Series, Die Set Catalog Number & (Number of Crimps)				
				MD7, MD6	35, 750	Y45	46	60
YDS6WA	6 (1)	3	161	W161 (2)	U161 (1)*	†	‡	–
YDS4WA	4 (1)	2-5/8	162	W162 (4)	U162 (1)*	†	‡	–
YDS2WA	2 (1)	3-7/8	163	W163 (6)	U163 (2)	†	‡	–
YDS6CA	6 (7)	3	161	W161 (2)	U161 (1)*	†	‡	–
YDS4CA	4 (7)	2-5/8	162	W162 (4)	U162 (1)*	†	‡	–
YDS2CA	2 (7)	3-7/8	163	W163 (6)	U163 (2)	†	‡	–
YDS25AT	1/0 (7)	7-1/4	BG 243	WBG (12) W243 (6)	UBG (6) U243 (3)	†	‡	–
YDS26AT	2/0 (7)	9-1/4	245	W245 (9)	U245 (5)	†	‡	–
YDS27AT	3/0 (7,19)	7-1/4	247	W247 (8)	U247 (4)	†	‡	L247 (3)
YDS28AT	4/0 (7, 19)	10-1/2	249	W249 (12)	U249 (6)	†	‡	L249 (3)
YDS29AT	250 (19)	7-1/2	616	–	U616 (6)	†	‡	–
YDS291AT	266.8 (7,19)	8-5/8	251	–	U251 (7)	†	‡	L251 (4)
YDS301AT	336.4 (19, 37)	9-7/8	321	–	U321 (8)	†	‡	L321 (4)
YDS31AT	350 (19)	11	490	–	U490 (9)	†	‡	L490 (3)
YDS311AT	397.5 (19)	12-1/4	468	–	U468 (10)	†	‡	–
YDS331AT	477 (19)	12-3/4	317	–	U317 (9)	†	‡	L317 (3)
YDS351AT	556.5 (19, 37)	12-3/4	261	–	U261 (9)	†	‡	L261 (3)
YDS361AT	636 (37)	13-1/2	469	–	–	S469 (8)	P469 (8)	L469 (4)
YDS391AT	795 (37), 800 (61)	13-5/8	342	–	–	S342 (8)	P342 (8)	L342 (4)
YDS431AT	954 (37, 61)	17-5/8	352	–	–	S352 (10)	P352 (10)	L352 (5)

* Multiple crimp die set; makes more than one crimp per tool compression. Figure indicates number of compressions.
† U Die with adapter PT6515.
‡ U Die with adapter PUADP1.

For faster installations use BURNDY® PATRIOT® family of battery tools, dies and cutters.



+51 991 872 290
Siguenos en nuestras redes
Escanea el QR
Visita nuestro Catálogo