Small Terminals


TYPE TP

VINYLUG™

Terminal - Polyvinylchloride
Insulated Ring Tongue
600 Volts Max., 105° C Max.

VINYLUG™ Type TP is designed for commercial and light duty industrial control and power circuit applications. Supplied with an expanded polyvinyl chloride (PVC) insulation shroud, many tongue variations and rated 600V makes TP terminals versatile and economical.





Features & Benefits

- Expanded insulation support accepts standard and large wire diameters
  ◊ Lowers inventory requirements, permits greater flexibility and provides insulation support
- Funnel entry
  ◊ Easy wire insertion
- Manufactured of pure electrolytic copper
  ◊ Provides maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Deep V groove serrations in the inner barrel
  ◊ Provides added holding strength and better conductivity
- Electro-tin plated
  ◊ Provides durable long-lasting corrosion resistance

Catalog Number	Wire Range (AWG/kcmil)	Stud Size	Dimensions				Installation Tooling	Wire Strip Length
			C	L	Y	Z		
TP16-4	22-16 Max. Insul. Dia.Accom.:.145 Color Code: Red	#3-#4	.22	.71	.61	.17	Plier Type: Y10D, Y10-22 or Ratchet Tool: MRE1022NV, MR8-89-1, MR8-G96, MR15	13/64
TP16-6		#4-#6	.25	.74	.62	.18		13/64
TP16-8		#6-#8	.31	.85	.70	.26		13/64
TP16-10		#8-#10	.31	.85	.70	.26		13/64
TP16-14		#12-1/4	.40	.99	.79	.36		13/64
TP16-516*		5/16	.47	1.11	.88	.41		13/64
TP16-38		3/8	.53	1.15	.88	.45		13/64
TP14-4	16-14 Max. Insul. Dia. Accom.:.180 Color Code: Blue	#4	.22	.53	.61	.17	Plier Type: Y10D, Y10-22 or Ratchet Tool: MRE1022NV, MR8-89-1, MR8-G96, MR15	13/64
TP14-6		#4-#6	.25	.74	.62	.18		13/64
TP14-8		#6-#8	.31	.85	.70	.26		13/64
TP14-10		#8-#10	.31	.85	.70	.26		13/64
TP14-14		#12-1/4	.40	.99	.79	.36		13/64
TP14-516		5/16	.53	1.15	.88	.45		13/64
TP14-38		3/8	.53	1.15	.88	.45		13/64
TP10-6	12-10 Max. Insul. Dia. Accom.:.260 Color Code: Yellow	#4-#6	.31	.68	.75	.20	Plier Type: Y10D, Y10-22 or Ratchet: MR8-89-1, MR15, M8ND w/N10HET-23	19/64
TP10-8		#6-#8	.36	1.00	.81	.26		19/64
TP10-10		#8-#10	.36	1.00	.81	.26		19/64
TP10-14		#12-1/4	.53	1.22	.95	.40		19/64
TP10-516		5/16	.53	1.22	.95	.42		19/64
TP10-38		3/8	.53	1.27	1.00	.45		19/64
TP10-12*		1/2	.69	1.51	1.17	.61		19/64

* Not UL Listed or CSA Certified.

+51 991 872 290
Siguenos en nuestras redes
Escanea el QR
Visita nuestro Catalogo