

# Large Range Taking COPPER CRIMPIT™ Types YC-C, YP-C

## Copper CRIMPIT™ Connector, Type YC-C for Copper, Copperweld

**Material: Copper UL Listed 90° C, Up to 35 kV ▲**

Range-taking compression tap connector made of pure copper. Designed to be gripped in the jaws or dies of installation tool, then slipped directly over line for easy installation. Also used for deadending applications.






RUS Accepted

**Copperweld-Copper Conductors**

8A - Use CRIMPIT™ accommodating 6 Str. Copper

6A - Use CRIMPIT™ accommodating 4 Str. Copper

4A - Use CRIMPIT™ accommodating 2 Str. Copper

2A - Use CRIMPIT™ accommodating 1/0 & 2/0 Copper

*** Multiple crimp die set. Makes more than one crimp per tool compression. Figure ( ) indicates number of compressions.*

*† Not UL Listed.*

*‡ Number of crimps.*

** U Die with adapter PUADP1.*

*§ Not UL Listed or CSA Certified with this conductor size in run.*


| Catalog Number | Run | Tap | L | ▲Die Index | Tools, Die Set, Catalog Number and (‡No. of Crimps) ▲ | | CRIMPIT™ for 1 Str. Copper | |
|---|---|---|---|---|---|---|---|---|
| | | | | | MD6 | 35, 750 Series, Y45, 46 Series* | Run | Tap |
| YC10C10 † | 12 Sol.-10 Str. | 12 Sol.-10 Str. | .32 | 238 | W238 (1) | U238 (1) | – | – |
| YC8C8 | 8 Sol.-8 Str. | 10 Sol.- 8 Str. | .50 | 162 | W162 (2) | U162** (1) | | |
| YC4C8 | 6 Sol.-4 Str. | 8 Sol.- 8 Str. | .62 | BG or 5/8 | BG (2) WBG** (1) | UBG (1) | – | – |
| YC4C6 | | 6 Sol.- 6 Str. | .57 | | | | | |
| YC4C4 | | 6 Sol.- 4 Str. | | | | | | |
| YC2C4 | 4 Sol.-2 Str. | 8 Sol.- 4 Str. | .67 | C | WC (2) | UC (1) | 1 Str. § | 6, 8 Str., 8 Sol. |
| YC2C2 | 2 Sol.-2 Str. | 2 Sol.- 2 Str. | | | | | – | – |
| YC26C2 | 1/0 Str.-2/0 Str. | 8 Sol.- 2 Str. | .92 | E or 0 | – | UE (3) U0 (1) | 1 Str. § | 1 or 2 Str. |
| YC26C26 | | 1/0 Str.- 2/0 Str. | | | | | – | – |
| YC28C2 | 3/0 Str.-4/0 Str. | 6 Sol.- 2 Str. | 1.07 | F or D3 | – | UF (3) UD3** (1) | – | – |
| YC28C26 | | 1/0 Str.- 2/0 Str. | | | | | | |
| YC28C28 | | 3/0.- 4/0 Str. | | | | | | |

## Copper CRIMPIT™ Tap Connector, Type YP-C for Copper

**Material: Copper**

Figure "6" shaped, wide range-taking copper compression tap connector for primary service taps and secondary service drops. Connector can be gripped in tool and slipped over the line for easy installation.






| Catalog Number | D | Run | Tap | Die Index | Tools, Die Set Catalog Number, & (# of Crimps) 35, 750 Series, Y45 †, 46 Series ‡ |
|---|---|---|---|---|---|
| YP2C2 | 0.75 | 6 Sol. - 2 Str. | 6 Sol. - 2 Str. | 0 | U0 (1) |
| YP28C28 | 1.00 | 2/0 Sol. - 4/0 Str. | 2/0 Sol. - 4/0 Str. | D3 | UD3 (1) |
| YP29C26 | 0.75 | 1/0 Sol. - 250 | 4 Sol. - 2/0 Str. | | |

*† U Die with adapter PT6515.*

*‡ U Die with adapter PUADP1.*

For faster installations use BURNDY® PATRIOT® family of battery tools, dies and cutters.





+51 991 872 290

Siguenos en nuestras redes

Escanea el QR
Visita nuestro Catálogo