

TYPE QP-F FINGRIP™

VINYL INSULATED FEMALE
QUICK DISCONNECTS

Material: Tin-Plated Brass
600 Volts Max., 105° C Max.

Vinyl Insulated Quick disconnects allows for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.



Features & Benefits

- Butted seam
- Insulated connectors
 - ◇ Eliminate the need for post installation insulation
- Funnel entry barrel opening
 - ◇ Assures quick and easy wire insertion
- Dimpled female socket detent
 - ◇ Ensures firm grip

Figure 1




Figure 2





Figure 3



Catalog Number	Figure	Wire Range	NEMA Tab Size	L	W	Installation Tool	Wire Strip Length
QP18F11X02D	3	18 - 22	.110 X .020	.75	.11	MRE1022NV Y1022 Y10D	3/8"
QP18F18X02D	2	18 - 22	.187 X .020	.79	.22		
QP18F25X03D	1	18 - 22	.250 X .032	.87	.29		
QP14F11X02D	3	14 - 16	.110 X .020	.75	.11	MRE1022NV Y1022 Y10D	3/8"
QP14F18X02D	2	14 - 16	.187 X .020	.79	.23		
QP14F25X03D	1	14 - 16	.250 X .032	.87	.29		
QP10F18X02D*	2	10 - 12	.187 X .020	.98	.29	MRE1022NV Y1022 Y10D	3/8"
QP10F25X03D	1	10 - 12	.250 X .032	.98	.29		
QP10F38X05D*	1	10 - 12	.375 X .047	1.12	.39		

* Not cULus.