Rigid and IMC Fittings

ORS Series One hole strap

Used to support rigid conduit and IMC, liquid tight flexible metallic conduit and liquid tight nonmetallic conduit (type B) to mounting surface. Stainless Steel straps available.

Standard Materials/Finishes

- Malleable Iron/zinc plated and Optional HDG
- Steel/Zinc Plated

Compliances and Certifications

- UL File No.E317579
- UL2239

Malleable Iron

ORS-M One hole strap-Malleable Iron-HDG optional with suffix -HDG(eg. ORS-50M-HDG)





Catalog Number	Trade Size	Dimensions A Inch	A mm	B Inch	B mm	C Inch	C mm
ORS-50M	1/2"	1.98	50.3	0.67	17.0	0.97	24.6
ORS-75M	3/4"	2.37	60.2	0.76	19.3	1.10	27.9
ORS-100M	1"	2.90	73.7	0.82	20.8	1.44	36.6
ORS-125M	1-1/4"	3.12	79.2	0.82	20.8	1.77	45.0
ORS-150M	1-1/2"	3.90	99.1	1.05	26.7	2.06	52.3
ORS-200M	2"	4.77	121.2	1.36	34.5	2.59	65.8
ORS-250M	2-1/2"	5.45	138.4	1.36	34.5	3.05	77.5
ORS-300M	3"	6.74	171.2	1.54	39.1	3.77	95.8
ORS-350M	3-1/2"	7.72	196.1	1.91	48.5	4.24	107.7
ORS-400M	4"	8.13	206.5	2.07	52.6	4.98	126.5
ORS-500M	5"	10.94	277.9	2.55	64.8	6.22	158.0
ORS-600M	6"	12.71	322.8	2.91	73.9	7.45	189.2

Steel

ORS-S One hole strap-Steel





Catalog Number	Trade Size	Dimensions A Inch	A mm	B Inch	B mm	C Inch	C mm	D Inch	D mm	
ORS-50S	1/2"	1.87	47.5	0.87	22.1	0.63	16.0	0.25	6.35	
ORS-75S	3/4"	2.23	56.6	1.05	26.7	0.74	18.8	0.31	7.874	
ORS-100S	1"	2.60	66.0	1.29	32.8	0.87	22.1	0.36	9.144	
ORS-125S	1-1/4"	2.98	75.7	1.62	41.1	0.87	22.1	0.36	9.144	
ORS-150S	1-1/2"	3.54	89.9	1.81	46.0	1.00	25.4	0.43	10.922	
ORS-200S	2"	4.14	105.2	2.28	57.9	1.13	28.7	0.54	13.716	
ORS-250S	2-1/2"	4.96	126.0	2.89	73.4	1.24	31.5	0.57	14.478	*
ORS-300S	3"	5.60	142.2	3.39	86.1	1.24	31.5	0.57	14.478	*
ORS-350S	3-1/2"	6.26	159.0	3.91	99.3	1.24	31.5	0.57	14.478	*
ORS-400S	4"	6.77	172.0	4.31	109.5	1.24	31.5	0.57	14.478	*