CB Series Conduit Bushings for Rigid Metal Conduit and IMC

Used with locknut to terminate threaded rigid conduit or IMC to a box or enclosure. Rounded surface of bushing prevents damage to wire insulation.

Rigid and IMC Fittings

Features

- ·Provide a smooth pulling surface
- ·Plastic Rating - 150°C for insulator

Standard Materials/Finishes

- ·GB: Zinc Die Cast
- ·GB-M: Malleable Iron
- ·Insulator: High Performance Thermoplastics

Compliances and Certifications

- ·UL File No.E256528
- ·UL514B
- ·NEMA FB-1
- ·Federal Specification A-A-50552

Zinc Die Cast

CB



Catalog Number			Dimensiones			
Non - Insulated	Insulated	Trade Size	A Inch	A mm	B Inch	B mm
CB-50	CBI-50	1/2"	1.04	26.4	0.38	9.7
CB-75	CBI-75	3/4"	1.31	33.3	0.41	10.4
CB-100	CBI-100	1"	1.58	40.1	0.50	12.7
CB-125	CBI-125	1-1/4"	1.90	48.3	0.53	13.5
CB-150	CBI-150	1-1/2"	2.16	54.9	0.56	14.2
CB-200	CBI-200	2"	2.67	67.8	0.66	16.8
CB-250	CBI-250	2-1/2"	3.23	82.0	0.75	19.1
CB-300	CBI-300	3"	3.85	97.8	0.75	19.1
CB-350	CBI-350	3-1/2"	4.36	110.7	0.75	19.1
CB-400	CBI-400	4"	4.87	123.7	0.75	19.1

Malleable Iron

CB-M





Catalog Number			Dimensiones			
Non - Insulated	Insulated	Trade Size	A Inch	A mm	B Inch	B mm
CB-50M	CBI-50M	1/2"	1.08	27.4	0.57	14.5
CB-75M	CBI-75M	3/4"	1.31	33.3	0.57	14.5
CB-100M	CBI-100M	1"	1.61	40.9	0.65	16.5
CB-125M	CBI-125M	1-1/4"	1.91	48.5	0.71	18.0
CB-150M	CBI-150M	1-1/2"	2.16	54.9	0.73	18.5
CB-200M	CBI-200M	2"	2.72	69.1	0.73	18.5
CB-250M	CBI-250M	2-1/2"	3.23	82.0	0.94	23.9
CB-300M	CBI-300M	3"	3.88	98.6	0.94	23.9
CB-350M	CBI-350M	3-1/2"	4.43	112.5	0.94	23.9
CB-400M	CBI-400M	4"	4.89	124.2	0.94	23.91
CB-500M	CBI-500M	5"	6.10	154.9	1.14	29.0
CB-600M	CBI-600M	6"	7.15	181.6	1.14	29.0

+51 991 872 290

Siguenos en **nuestras redes**

Escanea el QR
Visita nuestro **Catálogo**