Appleton®

DICOM INGENIEROS S.R.L.

Materiales eléctricos
Industriales

GUÍA DE
FICHAS TÉCNICAS

PRODUCTOS ELECTRICOS



MINERIA · ENERGIA · CONSTRUCCIÓN · HIDROCARBUROS · INDUSTRIA · TELECOMUNICACIONES · INFRAESTRUCTURA Y TRANSPORTE

Escanea el QR
Visita nuestro **Catálogo**

Siguenos en **nuestras redes**

+51 991 872 290

Industrial Areamaster™ Generation 2 and High Lumen LED Series Luminaires

Floodlight

Ordinary Locations

NEC/CEC/NOM: Type 3R, 4, 4X | IP66/67 | Marine outside type (salt water) for USA Only | Wet locations
IECEE CB: IK08 | IP66
Markings: CE | UKCA
Notable: American Bureau of Shipping (ABS) Certified | 10G Vibration

Accessories and Replacement Parts

	Description	Weight in kg (lbs)	Catalog Number
Crossarm Mounting Bracket			
	Has 180° horizontal adjustment — degree marked. Facilitates mounting floodlight to crossarm or other flat surface, or to GAM8WB. Includes floodlight yoke bolts. Malleable iron, zinc plated, chromate sealed, architectural bronze polyester finish.	1.4 (3.1)	**GAM8CA**
Pipe or Wall Mount Bracket			
	Used with GAM8CA. Clamps to 1" to 2-1/2" pipe, vertical or horizontal, or mounts on flat surfaces. Includes U-bolt and crossarm bracket bolts. Malleable iron, zinc plated, chromate sealed, with architectural bronze polyester finish.	2.9 (6.4)	**GAM8WB**
	*Crossarm Mounting Bracket (**GAM8CA**) used with Pipe or Wall Mount Bracket (**GAM8WB**).*		
Poletop Slip-Fitter			
	Slip-fits 1" or 1-1/2" pipe size poletop tenons. Includes floodlight yoke bolts, 3 locking bolts, and cord grip. Body is malleable iron-zinc plated, chromate sealed, with cast aluminum cap. Assembly has architectural bronze polyester finish.	2.4 (5.3)	**AMLEDSF1**
Poletop Slip-Fitter			
	Slip-fits 2" or 2-1/2" poletop tenons. Includes floodlight yoke bolts, 3 locking bolts, and cord grip. Malleable iron, zinc plated, chromate sealed, with architectural bronze polyester finish.	2.8 (6.2)	**GAM8SF**


Industrial Areamaster™ Generation 2 and High Lumen LED Series Luminaires

Floodlight

Ordinary Locations

NEC/CEC/NOM: Type 3R, 4, 4X | IP66/67 | Marine outside type (salt water) for USA Only | Wet locations
IECEE CB: IK08 | IP66
Markings: CE | UKCA
Notable: American Bureau of Shipping (ABS) Certified | 10G Vibration

Accessories and Replacement Parts

	Description	Weight in kg (lbs)	Catalog Number
Wall Mount Bracket			
	Used with GAM8SF to provide a wall mounting option. Galvanized Steel.	4.8 (10.5)	**GPSWB6GAL**
Wire Guard			
	Stainless steel.	0.2 (0.4)	**LGGUARD** **LHGUARD**
Safety Cable			
	Stainless steel.	0.2 (0.4)	**LEDSC**
Visor			
	Steel with architectural bronze polyester finish. For Dark Sky Friendly design.	0.2 (0.4)	**AMLGV** **AMLHV**
Portable Floodlight Base			
	Portable floodlight base for temporary lighting applications. To be used with wire guard. Malleable iron with architectural bronze polyester finish.	2.4 (5.2)	**GAMPFB**
Replacement Covers/Lenses			
	Clear Glass — IAMLGL6, IAMLGL7, IAMLGL8	2.2 (4.8)	**AMLGCLEAR**
	Frosted Glass — IAMLGL6, IAMLGL7, IAMLGL8	2.0 (4.5)	**AMLGFROST**
	Diffused Polycarbonate — IAMLGL6, IAMLGL7, IAMLGL8	1.6 (3.5)	**AMLGDIFFP**
	Clear Glass — IAMLHL1, IAMLHL2, IAMLHL3	2.4 (5.3)	**AMLHCLEAR**
	Frosted Glass — IAMLHL1, IAMLHL2, IAMLHL3	2.4 (5.3)	**AMLHFROST**
Yoke Mount Bracket			
	Stainless Steel Yoke Mount Bracket. For installations requiring a higher degree of corrosion protection. Made with all stainless steel components, no painted finish.	1.8 (4.0)	**AMLYMSS**
	Architectural Bronze Replacement Yoke Bracket	1.41 (3.1)	**AMLYMAB**
	Architectural Bronze Replacement Yoke Bracket - Matches mounting hole pattern of Crouse-Hinds™ ✣ Champ FMVA and Champ Pro PFMA LED series floodlights	1.41 (3.1)	**AMLYMCH**

✣ *Crouse-Hinds and Champ are registered trademarks of Eaton.*